

FT-VP series Double servo motor vertical packing machine

Providing A Full Range Of Automatic Packaging System Solutions.



Feature

- PLC control, man-machine interface, easy to operate and maintain.
- Driven by double servo motor and optical tracking devices to keep high packing speed and high accuracy.
- The frame of machine is made of #304 stainless steel, equipped with auto-stop protection function when open the door.

Application

- Applicable bag type: Pillow bag, Gusset bag, Seal type bag.
- Applicable film materials: A variety of laminated films, single-layer PE film, Film thickness range 0.04mm-0.15mm.
- Applicable packing materials: A variety of recreation food, frozen food, coffee beans, oatmeal, granulated sugar, salt, rice, pet food, small hardware etc.



Specifications

Model	FT-VP3220	FT-VP4230	FT-VP5235	FT-VP6240	FT-VP7245
Film width	140 ~ 320mm	160 ~ 420mm	180 ~ 520mm	180 ~ 620mm	200 ~ 720mm
Bag size	L*W=(60 ~ 200)mm*(50 ~ 150)mm	L*W=(60 ~ 300)mm*(60 ~ 200)mm	L*W=(60 ~ 350)mm*(70 ~ 250)mm	L*W=(70 ~ 400)mm*(80 ~ 300)mm	L*W=(70 ~ 450)mm*(80 ~ 350)mm
Maximum packing speed	100bags/min	100bags/min	90bags/min	85bags/min	70bags/min
Power requirement	2.9KW/220V/50(60)Hz	4.5KW/220V/50(60)Hz	4.5KW/220V/50(60)Hz	5.1KW/220V/50(60)Hz	5.5KW/220V/50(60)HZ
Gas pression	0.6MPa	0.6MPa	0.6MPa	0.6MPa	0.6MPa
Gas consumption	0.15m ³ /min	0.2m ³ /min	0.2m ³ /min	0.2m ³ /min	0.4m ³ /min
Machine size	L*W*H=1158mm*930mm*1213mm	L*W*H=1400mm*1100mm*1560mm	L*W*H=1514mm*1154mm*1590mm	L*W*H=1640mm*1226mm*1709mm	L*W*H=1748mm*1344mm*1955mm
Machine weight	350Kg	500Kg	550Kg	600Kg	680Kg