

# FT-PR series premade bag rotary packing machine

Providing A Full Range Of Automatic Packaging System Solutions.



## Feature

- Automatic warning protect function, safer working environment and less materials lossing.
- The frame of machine is made of #304 stainless steel, man-machine interface, easy to operate and maintaince.
- Available system for choice: remote diagnosis system, automatic lubrication system, automatic clips adjusting system.

## Application

- Applicable Bag Type: side sealing, standup pouch, zipper bag, handbag, paper bag and other bags.
- Applicable Film Material: a variety of laminated films, film thickness range 0.04~0.09mm.



## Specifications

Model	FT-PR200C	FT-PR260C	FT-PR300B
Station No.	8 stations	8 stations	6 stations
Weighing Range	10~2500g	10~2500g	10~2500g
Packing Speed	10~60bags/min	10~60bags/min	10~60bags/min
Bag Size	L: ≤350mm W: 100~220mm	L: ≤400mm W: 140~260mm	L: ≤450mm W: 200~320mm
Station Function	bag feeding, date printing, bag opener, products filling, backup, backup, sealing, output	bag feeding, date printing, bag opener, products filling, backup, backup, sealing, output	bag feeding, date printing, bag opener, products filling, sealing, output
Gas Pression	0.8MPa	0.8MPa	0.8MPa
Gas Consumption	0.6m <sup>3</sup> /min	0.6m <sup>3</sup> /min	0.6m <sup>3</sup> /min
Power Requirement	2.5KW/380V/50(60)Hz	2.5KW/380V/50(60)Hz	2.5KW/380V/50(60)Hz
Machine Size	L*W*H=1610*1510*1480mm	L*W*H=1640*1510*1510mm	L*W*H=1610*1510*1480mm
Machine Weight	1350KG	1400KG	1500KG