

FT-DP series zip-lock standup bag packing machine

Providing A Full Range Of Automatic Packaging System Solutions.



Feature

- PLC control, man-machine interface, easy to operate and maintain.
- Driven by servo motor and optical tracking devices to keep accuracy.
- The frame of machine is made of #304 stainless steel, equipped with auto-stop protection function when open the door.

Application

- Applicable Bag Type: oval standup bag with or without zip-lock.
- Applicable Film Material: a variety of laminated films. Film thickness range is 0.04~0.15mm.
- Applicable Packing Material: a variety of recreation food, frozen food, coffee beans, oatmeal, granulated sugar, salt, rice, pet food, small hardware etc.



Specifications

Model	FT-DP5220	FT-DP7230
Max. Film Width	250~520mm	250~720mm
Bag Size Range	L*W=(100 ~ 235)mm*(50 ~ 200)mm	L*W=(100 ~ 335)mm*(50 ~ 300)mm
Bag Bottom Width	30~60mm	40 ~ 100mm
Packing Speed	5~40bags/min	5 ~ 40bags/min
Power Requirement	5KW/220V/50(60)HZ	6KW/220V/50(60)HZ
Gas Pressure	0.6~0.8MPa	0.6~0.8MPa
Gas Consumption	0.4m ² /min	0.6m ² /min
Machine Size(L*W*H)	2015mm*1650mm*1910mm	2150mm*1710mm*2040mm
Machine Weight	550KG	700KG