

FT-E series Economic vertical packing machine

Providing A Full Range Of Automatic Packaging System Solutions.



Feature

- ⦿ PLC control, man-machine interface, easy to operate and maintain.
- ⦿ Driven by servo motor and optical tracking devices to keep accuracy.
- ⦿ The frame of machine is made of #304 stainless steel, equipped with auto-stop protection function when open the door.

Application

- ⦿ Applicable bag type: Pillow bag, Gusset Bag, Seal type bag.
- ⦿ Applicable film materials: A variety of laminated films, single-layer PE film, Film thickness range 0.04mm~0.15mm.
- ⦿ Applicable packing materials: A variety of recreation food, frozen food, coffee beans, oatmeal, granulated sugar, salt, rice, pet food, small hardware etc.



Specifications

Model	FT-E3220	FT-E4230	FT-E5235	FT-E6240	FT-E7245
Film width	140 - 320mm	160 - 420mm	180 - 520mm	180 - 620mm	200 - 720mm
Bag size	L*W=(60 - 200)mm*(50 - 150)mm	L*W=(60 - 300)mm*(60 - 200)mm	L*W=(60 - 350)mm*(70 - 250)mm	L*W=(70 - 400)mm*(80 - 300)mm	L*W=(70 - 450)mm*(80 - 350)mm
Maximum packing speed	70bags/min	65bags/min	60bags/min	50bags/min	0 - 70bags/min
Power requirement	2.15KW/220V/50(60)Hz	3.4KW/220V/50(60)Hz	3.4KW/220V/50(60)Hz	3.6KW/220V/50(60)Hz	5.5KW/220V/50(60)Hz
Gas pression	0.6Mbra	0.6Mbra	0.6Mbra	0.6Mbra	0.6MPa
Gas consumption	0.5m ³ /min	0.6m ³ /min	0.7m ³ /min	0.8m ³ /min	0.4m ³ /min
Machine size	L*W*H=1158mm*930mm*1213mm	L*W*H=1465mm*1040mm*1470mm	L*W*H=1540mm*1160mm*1600mm	L*W*H=1640mm*1226mm*1709mm	L*W*H=1748mm*1344mm*1955mm
Machine weight	350Kg	400Kg	450Kg	550Kg	630Kg